

25X1A ORIG: [REDACTED] Approved For Release 2002/10/16 : CIA-RDP71B00822R000200040003-0

25X1A UNIT: **ASD/OSA**

25X1A EXT: [REDACTED]

25X1A DATE: **9 MARCH 1965**

25X1A TO: [REDACTED]

FROM: **DIRECTOR**

CONF:

INFO:

CLASSIFIED MESSAGE

SECRET

ROUTING	
1	ASD/OSA 9
2	ASD/OSA 10
3	D/TECH/OSA 11
4	AD/OSA 12
5	D/FA/OSA 13
6	OXC/OSA 14
7	RB/OSA 15
8	16

P R O C E S S I N G	DEFERRED	PRIORITY	INITIALS
	X ROUTINE	OPERATIONAL IMMEDIATE	INITIALS

25X1A TO: [REDACTED]

25X1A INFO: [REDACTED]

25X1A OXCART [REDACTED]

25X1A REF: [REDACTED] [REDACTED] (IN 75659)

25X1A

0760

25X1A 25X1A

05A1-15

MAXIMUM MEASURED GROUND OVERPRESSURES FROM A-12 AT 65,000 FEET DO NOT EXCEED ONE POUND PER SQUARE FOOT. THIS IS EQUIVALENT TO CLOSE RANGE THUNDER AND POSSIBLY SOME WINDOW DAMAGE. INCREASED ALTITUDES REDUCE OVERPRESSURES AND CORRESPONDING EFFECTS. NO PROBLEMS ANTICIPATED DUE TO SONIC BOOMS DURING OVERFLIGHTS OF DAMS ON TRAINING MISSIONS.

END OF MESSAGE

25X1A

ASD/OSA

RELEASING OFFICER

COORDINATING OFFICERS

SECRET

AUTHENTICATING OFFICER

REPRODUCTION BY OTHER THAN THE ISSUING OFFICE IS PROHIBITED.

25X1A

HANDLE VIA
CONTROL SYSTEM

SECRET
OXCART

Copy 4

25X1A

MEMORANDUM FOR: Deputy Director for Science and Technology
SUBJECT: Sonic Boom Measurements

1. Sonic boom measurements of OXCART aircraft are being recorded in the vicinity of on an opportune, non-interference basis by Lockheed personnel using Lockheed ground measuring equipment. These measurements are being taken compatible with the current flight test and operational readiness program. Recent sonic boom overpressures recorded of SKYLARK aircraft in the SKYLARK environment, i.e., 2.8 Mach and 78,000 feet altitude, are 0.75 pounds per square foot nominal and a minimum of 0.3 pounds per square foot is direct overflight of the recording station. This nominal value is approximately double the volume theory but lower than the lowest overpressure recorded for the B-58 aircraft at comparable altitudes and lower speeds. During the climb-out portion of the flight profile at approximately 1.5 Mach and 30,000 feet altitude, overpressures as high as 4-5 pounds per square foot have been recorded. Lateral displacement of the flight path from directly over the recording station results in lower overpressures than those quoted above. Although the 2.8 Mach and 78,000 foot overpressures are comparatively small, this magnitude will definitely be heard on the ground. All of the above data have been transmitted to the FAA and NASA. (See Attachment)

25X1A

2. It is recommended that this Agency conduct no specific sonic boom measurements tests for the Supersonic Transport Program but continue to forward all results of A-12 overpressure recordings to the FAA/NASA for information. Future measurements will also include overpressures recorded during the deceleration phase of the flight profile.

JACK C. LEDFORD
Colonel USAF
Assistant Director
(Special Activities)

OXCART
SECRET

HANDLE VIA
CONTROL SYSTEM

25X1A

ILLEGIB

Approved For Release 2002/10/16 : CIA-RDP71B00822R000200040003-0

Next 1 Page(s) In Document Exempt

Approved For Release 2002/10/16 : CIA-RDP71B00822R000200040003-0